

1. PUNCH  $\frac{3}{16}$ "  $\phi$  HOLES IN THE TOP FLANGE OF ALL BEAMS 2'-0" O.C.  
    STAGGER HOLES. FASTEN NAILERS WITH  $\frac{1}{2}$ "  $\phi$  BOLTS.
2. FILL 6 STRUCT. TUBE COLUMNS WITH GROUT AFTER ERECTION

DETAIL A

|                                                                   |                                                     |                                                      |
|-------------------------------------------------------------------|-----------------------------------------------------|------------------------------------------------------|
| STEEL FRAMING DETAILS                                             |                                                     |                                                      |
| CITY OF HARTFORD CONNECTICUT<br>DEPARTMENT OF ENGINEERING         |                                                     |                                                      |
| FIELD HOUSE, SHELTER,<br>& SPRAY POOL AT<br>BARBOUR-KENEY COMPLEX |                                                     | DWG. NO.<br><br><b>S-1</b>                           |
| SUBMITTED<br><i>Paul B. Anthony</i>                               | RECOMMENDED<br><i>[Signature]</i><br>CITY ARCHITECT | APPROVED<br><i>Samuel C. Hooper</i><br>CITY ENGINEER |
| DESIGN <u>PDA</u>                                                 | DRAWN <u>PDA</u>                                    | DAYBOOK NO. <u>010153D</u>                           |
| TRACED                                                            | CHECK                                               | DATE <u>MARCH 6, 1970</u>                            |