



PERMISSIBLE SOURCES OF EMBANKMENT MATERIAL	
AREA	TYPE OF MATERIAL
BORROW AREA "H"	Formation composed of two types, (1) coarse to fine silt, and (2) mixed materials graded from gravel and coarse sand to fine silt. Materials suitable for impervious blanket construction.
BORROW AREA "L"	Formation composed chiefly of coarse to medium sand suitable for random embankment construction.

12-31-45	As built				
DATE	REVISION	REV BY	CK BY	AP BY	

CONNECTICUT RIVER FLOOD CONTROL	
CLARK DIKE	
AVIATION ROAD-900 FEET NORTH	
BORROW AREAS	
HARTFORD, CONNECTICUT	
CONNECTICUT RIVER,	CONNECTICUT
IN 7 SHEETS	SHEET NO. 2
SCALE: 1 IN. = 1000 FT.	
U. S. ENGINEER OFFICE, PROVIDENCE, R. I. SEPT., 1939	
SUBMITTED HEAD, GEOLOGY SECTION	APPROVAL PRINCIPAL ENGINEER CHIEF, F. C. ENGINEERING DIV.
COMPILED ASST. ENGINEER	DRAWN BY TRACED BY L. A. O. F. C. CHECKED BY W. A. F. C.
FILE NO. C-2-1186	