

NOTES:

INSTALL 6' OF 6"x20" GRANITE CURB ON EACH SIDE OF CATCH BASIN WHERE INSTALLING BITUMINOUS CONCRETE LIP CURBING

- (B) CONSTRUCT BITUMINOUS CONCRETE DRIVEWAY RAMP
- (C) CONSTRUCT 8" REINFORCED CONCRETE DRIVEWAY RAMP
- (E) EXISTING DRIVEWAY RAMP TO REMAIN

CALL BEFORE YOU DIG - THE CONTRACTOR IS HEREBY REMINDED THAT TITLE 16 CHAPTER 293 OF THE CONNECTICUT GENERAL STATUTES REQUIRES NOTIFICATION TO UTILITY COMPANIES OF PENDING EXCAVATION AT OR NEAR PUBLIC UTILITIES. THE CONTRACTOR SHALL CALL 1-800-922-4455 AT LEAST 48 HOURS PRIOR TO EXCAVATION.

APPROX. LIMIT OF CONSTRUCTION
STA. 10+52.5 BRANFORD STREET C

EXCAVATE EXISTING PAVEMENT 12" BELOW FINISHED GRADE, CONSTRUCT 8" PROCESSED TRAPROCK SUBBASE, 2 1/2" PREMIXED BIT. CONC. BASE AND 1 1/2" BIT. CONC. SURFACE COURSE (CLASS II) STA. 10+52.5 TO STA. 14+50

INSTALL GEOTEXTILE FABRIC PRIOR TO PLACING SUBBASE
STA. 10+52.5 TO STA. 14+50

INSTALL STOP BAR
(12" WHITE PREFORMED PLASTIC PAVEMENT MARKINGS)

INSTALL 6" BIT CONC. LIP CURBING

FROM STA. 10+78 TO STA. 14+50

(EXCEPT DRIVEWAYS AND CATCH BASINS)

REMOVE EXISTING CONC. CURB AND GUTTER

FROM STA. 10+78 TO STA. 14+50

CONSTRUCT NEW 8" REINF. CONC. SIDEWALK RAMP (TYPE 2)

5" CONC. WALK AND RESET RADIUS GRANITE CURB

FROM STA. 10+78 TO STA. 14+50

REMOVE EXISTING CONC. CURB AND GUTTER

FROM STA. 10+78 TO STA. 14+50

INSTALL 6" BIT CONC. LIP CURBING

FROM STA. 10+78 TO STA. 14+50

(EXCEPT DRIVEWAYS AND CATCH BASINS)

CONSTRUCT NEW 8" REINF. CONC. SIDEWALK RAMP (TYPE 2)

5" CONC. WALK AND INSTALL NEW 6"x20" RADIUS GRANITE CURB

FROM STA. 10+78 TO STA. 14+50

REMOVE EXISTING CONC. CURB AND GUTTER

FROM STA. 10+78 TO STA. 14+50

INSTALL 6" BIT CONC. LIP CURBING

FROM STA. 10+78 TO STA. 14+50

(EXCEPT DRIVEWAYS AND CATCH BASINS)

CONSTRUCT NEW 8" REINF. CONC. SIDEWALK RAMP (TYPE 2)

5" CONC. WALK AND INSTALL NEW 6"x20" RADIUS GRANITE CURB

FROM STA. 10+78 TO STA. 14+50

REMOVE EXISTING CONC. CURB AND GUTTER

FROM STA. 10+78 TO STA. 14+50

INSTALL 6" BIT CONC. LIP CURBING

FROM STA. 10+78 TO STA. 14+50

(EXCEPT DRIVEWAYS AND CATCH BASINS)

CONSTRUCT NEW 8" REINF. CONC. SIDEWALK RAMP (TYPE 2)

5" CONC. WALK AND INSTALL NEW 6"x20" RADIUS GRANITE CURB

FROM STA. 10+78 TO STA. 14+50

REMOVE EXISTING CONC. CURB AND GUTTER

FROM STA. 10+78 TO STA. 14+50

INSTALL 6" BIT CONC. LIP CURBING

FROM STA. 10+78 TO STA. 14+50

(EXCEPT DRIVEWAYS AND CATCH BASINS)

CONSTRUCT NEW 8" REINF. CONC. SIDEWALK RAMP (TYPE 2)

5" CONC. WALK AND INSTALL NEW 6"x20" RADIUS GRANITE CURB

FROM STA. 10+78 TO STA. 14+50

REMOVE EXISTING CONC. CURB AND GUTTER

FROM STA. 10+78 TO STA. 14+50

INSTALL 6" BIT CONC. LIP CURBING

FROM STA. 10+78 TO STA. 14+50

(EXCEPT DRIVEWAYS AND CATCH BASINS)

CONSTRUCT NEW 8" REINF. CONC. SIDEWALK RAMP (TYPE 2)

5" CONC. WALK AND INSTALL NEW 6"x20" RADIUS GRANITE CURB

FROM STA. 10+78 TO STA. 14+50

REMOVE EXISTING CONC. CURB AND GUTTER

FROM STA. 10+78 TO STA. 14+50

INSTALL 6" BIT CONC. LIP CURBING

FROM STA. 10+78 TO STA. 14+50

(EXCEPT DRIVEWAYS AND CATCH BASINS)

CONSTRUCT NEW 8" REINF. CONC. SIDEWALK RAMP (TYPE 2)

5" CONC. WALK AND INSTALL NEW 6"x20" RADIUS GRANITE CURB

FROM STA. 10+78 TO STA. 14+50

REMOVE EXISTING CONC. CURB AND GUTTER

FROM STA. 10+78 TO STA. 14+50

INSTALL 6" BIT CONC. LIP CURBING

FROM STA. 10+78 TO STA. 14+50

(EXCEPT DRIVEWAYS AND CATCH BASINS)

CONSTRUCT NEW 8" REINF. CONC. SIDEWALK RAMP (TYPE 2)

5" CONC. WALK AND INSTALL NEW 6"x20" RADIUS GRANITE CURB

FROM STA. 10+78 TO STA. 14+50

REMOVE EXISTING CONC. CURB AND GUTTER

FROM STA. 10+78 TO STA. 14+50

INSTALL 6" BIT CONC. LIP CURBING

FROM STA. 10+78 TO STA. 14+50

(EXCEPT DRIVEWAYS AND CATCH BASINS)

CONSTRUCT NEW 8" REINF. CONC. SIDEWALK RAMP (TYPE 2)

5" CONC. WALK AND INSTALL NEW 6"x20" RADIUS GRANITE CURB

FROM STA. 10+78 TO STA. 14+50

REMOVE EXISTING CONC. CURB AND GUTTER

FROM STA. 10+78 TO STA. 14+50

INSTALL 6" BIT CONC. LIP CURBING

FROM STA. 10+78 TO STA. 14+50

(EXCEPT DRIVEWAYS AND CATCH BASINS)

CONSTRUCT NEW 8" REINF. CONC. SIDEWALK RAMP (TYPE 2)

5" CONC. WALK AND INSTALL NEW 6"x20" RADIUS GRANITE CURB

FROM STA. 10+78 TO STA. 14+50

REMOVE EXISTING CONC. CURB AND GUTTER

FROM STA. 10+78 TO STA. 14+50

INSTALL 6" BIT CONC. LIP CURBING

FROM STA. 10+78 TO STA. 14+50

(EXCEPT DRIVEWAYS AND CATCH BASINS)

CONSTRUCT NEW 8" REINF. CONC. SIDEWALK RAMP (TYPE 2)

5" CONC. WALK AND INSTALL NEW 6"x20" RADIUS GRANITE CURB

FROM STA. 10+78 TO STA. 14+50

PLAN

APPROX. LIMIT OF CONSTRUCTION
STA. 10+52.5 BRANFORD STREET C

EXISTING BACK OF WALK
EXISTING FRONT OF WALK
EXISTING FRONT OF WALK
EXISTING GUTTER

GRADE TO MATCH EXISTING

GRADE TO MATCH EXISTING

GRADE TO MATCH EXISTING

PROFILE

PROPOSED TOP OF CURB

PROPOSED GUTTER

PROPOSED

PROPOSED TOP OF CURB

PROPOSED GUTTER

NOTE:
TOP OF CURB SHALL FOLLOW 6" ABOVE GUTTER GRADE (TYP.)

SUPV. ARN	
DESIGN AC IDH	
DRAWN KHT	
CHECKED JAC	
DATE 6-25-85	
NO.	DATE
DESCRIPTION	
REVISIONS	

GRAPHIC SCALES
HORIZ. 1" = 20'
VERT. 1" = 2'

ROADWAY RECONSTRUCTION
HARTFORD, CONNECTICUT



Hayden | Wegman
Consulting Engineers

WEST HARTFORD
NEW YORK • BOSTON • BUFFALO
ATLANTA • MEMPHIS

CITY OF HARTFORD, CONNECTICUT
DEPARTMENT OF PUBLIC WORKS
BUREAU OF ENGINEERING SERVICES

DRAWN
CHECKED
SCALE
DAYBOOK NO. Q10956
DATE

BRANFORD STREET
STA. 10+52.5 TO STA. 14+50

PLAN AND PROFILE

Contract #E85-34 Job No. 845304 OF 3